

## VIBROINSULATION ACOUSTIC SEALING COMPOUND SONETIC STANDART GOST 25621-83 CUSTOM CODE 3214101009



### DESCRIPTION

SONETIC - is a monocomponent silicone compound for sealing joints and seals in framed and non-framed constructions as walls, sealings, partition walls. The compound is used for lowering vibration rate transferred trough firm elements in sound insulation systems, exceeds sound proofing of the construction.

### INGRIDIENTS

- polydimethylsiloxan;
- indirect component;
- sealing component.

### PACKAGE SIZE AND WEIGHT

Item	Tube height*, mm	Tube diameter, mm	Tube volume*,m <sup>3</sup>	Volume, ml	Tube weight, kg
Sonetic	215	48	0,00038	310	0,35

\*The volume and height are given without the size of screwhead and plastic cap.

### TECHNICAL CHARACTERISTICS

Characteristics	Sonetic
Dynamic elasticity coefficient under loading, mP	not more than two
Scent	no scent after hardening
Color	white
Dissolution in water	Non-dissolving
Burning temperature, °C	>400
Density, gr/sm <sup>2</sup>	1,02 for temp 23 °C

### RECOMMENDED FOR

- the compound is used for framed and non-framed systems of sound insulation for cealing joints, seals and bindings;
- implemented for reduction of transferred sound vibrations and exceeding soundproofing of the construction.

### FEATURES

- excellent vibroinsulation and acoustic qualities;
- firm adhesive to the majority of materials used in construction ( metal, plastic, glass and etc.);
- UF resistant;
- guaranteed sealing of joints of any size;
- scent free;
- friendly.

### SAFETY REQUIREMENTS

No special safety measures are required but nevertheless it is recommended:

- in case of contact with skin the compound should be raised with tissue or paper, washed away with water and soap;
- in case of contact with eyes shold be washed with water.

### CERTIFICATE

1. Certificate of Russian standard.

### EXPIRING DATE

18 months after production date.

### PACKAGING AND TRANSPORT STANDARDS

Item	Package	Quantity of tubes, pcs	Size of package, mm	Weight of box, kg	Volume of package, m <sup>3</sup>
Sonetic	box	25	260x260x240	8,75	0,016

Material is loaded into the truck multiple of boxes. Cargo hazard class - safe cargo.