

## STANDARD P PARTITION SOUNDPROOFING SYSTEM

from Album of Typical Technical Solution  
TechnoSonus and NIISF version  
TS/01.2020/RD/S/R4 type TS-1.2



SYSTEM  
THICKNESS  
**103 mm**



GENERAL CONSTRUCTION  
SOUND REDUCTION INDEX  
**Rw = 56 dB**



### DESCRIPTION

The system of advanced efficiency for rooms partitioning. Used in hotels, offices, conference rooms, manufacturing departments, etc. The system ensures the best soundproofing effect against airborne noise. The main system elements are thin and heavy panels Sonoplat.

### COMPONENTS

Material	Coefficient per 1 m <sup>2</sup> *
SonoPlat Standard Plus Panel (1.2m x 0.8m x 12mm) 0.96m <sup>2</sup>	2,1875
StopZvuk BP Premium Sound Absorbing Board (1m x 0.6m x 50mm) 4pcs., 2.4m <sup>2</sup>	0,4167
Sonetic Vibroacoustic Sealant, 310ml	0,5000
SonoPlat Band (40m x 50mm) w/o logo	0,1538
Vibration Cushioning Band V-100 (30m x 100mm x 4mm)	0,0450
Vibration Isolation Washer (14mm x 5mm) + metal washer (M6) 50 pcs.	0,1429
Sealing Band DB (30m x 50mm x 2.5mm)	0,2470
AcousticGyps PN Reinforced Profile 50/40, 3m	0,4500
AcousticGyps PS Reinforced Profile 50/50, 3m	1,6000
AcousticGyps Soundproofing Gypsum Board (2m x 1.2m x 12.5mm) 2.4m <sup>2</sup>	0,9167
Self-Threading Screw TC-M 3.5x25 (500 pcs.)	0,1000
Self-Threading Screw TC-XTN 3.9x38 (500 pcs.)	0,1600
Self-Threading Screw TC-MM 4.2x13 (1000 pcs.)	0,0150
Dowel Nail TC-DG 6/60 (100 pcs.)	0,0700

\*Coefficients are advisory in nature, calculated empirically